

ALITHERM 400 FLUSH SASH WINDOW ORDER/QUOTE FORM

Please tick for quote only Page ___ of

Aluminium Direct Fax: 01453 827801 E-mail Orders: sop@customade.co.uk

Company Name (Acc No): _____

Signature: _____

Preferred Delivery Date: _____

Print Name: _____

Order Ref: _____

Date: _____ E-mail confirmation: _____

(Please tick):
 Alitherm 400i Flush Sash [] -Contemporary frame - flat sash - **INTERNALLY GLAZED** - square bead with dummy sashes

Note: Alitherm 400i triple glazed windows are wedge gasketed as standard.

Please Circle Items Required

<p>(Q) = Selection may need to be upgraded to meet Part Q</p> <p>Part Q Compliant: Y / N</p> <p>Colour: White (G) / Grey (7016M) / Black (9005M) / Dual Grey Ex (M) & White Int (G)</p> <p>Handle Colour: White / Gold / Chrome / Black / Grey / Satin Silver / Graphite / Antique Black (Monkey tail)</p> <p>Stayguards^(Q): Y / N</p> <p>Trickle Vent Colour: White / Black / Grey / Silver / Grey on white Trickle vent widths 2700mm²=300mm, 4000mm²=400mm and 5000mm²=600mm</p> <p>Drainage: Face / Concealed</p>	<p>Glass Supply: YES / Unglazed</p> <p>Glass specification width^(Q): 28mm DGU 28.8mm lam DGU</p> <p>Triple glazing- Alitherm 400i only: 40mm TGU 40.8mm lam TGU</p> <p><u>If unglazed please tick above glass thickness for gasket type.</u></p> <p>Standard Thermal Rating: Window Energy Rating A externally glazed and B internally glazed with 28mm Clear, 1.2 Softcoat, Argon, Black W/edge (Q)</p> <p>Product U value Special Requirements: _____</p> <p>Astragal bars for 28mm units only - please tick: [] 25mm Flat bar</p>
--	--

Hinge codes: S=Standard / E=Egress easy / R=Restrictor / RE=Restrictor Egress (TRI R90)
 T/V Trickle vents require a 30 or 42mm add-on, fixed to the top of the window

Location	Design (viewed outside, please show T/vents and mullion/transom dimensions)	Qty	Sizes (mm) Including Cills & Add-ons	Cill	Hinge		Glass Spec (Tgh, Obs, Lead)	Add ons (30 or 42mm required with t/vents)			Special Requirements	
					S	E		20mm	30mm	42mm		
			W	None	S	E		T				
												H
			150	2700	4000	5000						
												190 / 225
			W	None	S	E		T				
												H
			150	2700	4000	5000						
												190 / 225
			W	None	S	E		T				
												H
			150	2700	4000	5000						
												190 / 225

Location	Design (viewed outside , please show T/vents and mullion/transom dimensions)	Qty	Sizes (mm) Including Cills & Add-ons		Cill	Hinge	Glass Spec (Tgh, Obs, Lead)	Add ons 20mm 30mm 42mm (30 or 42mm required with t/vents)			Special Requirements
						T/V					
			W		None 85	S E R RE		T			
			H		150 190 / 225	2700 4000 5000		B			
			H		150 190 / 225	2700 4000 5000		L			
			H		190 / 225	5000		R			
			W		None 85	S E R RE		T			
			H		150 190 / 225	2700 4000 5000		B			
			H		150 190 / 225	2700 4000 5000		L			
			H		190 / 225	5000		R			
			W		None 85	S E R RE		T			
			H		150 190 / 225	2700 4000 5000		B			
			H		150 190 / 225	2700 4000 5000		L			
			H		190 / 225	5000		R			
			W		None 85	S E R RE		T			
			H		150 190 / 225	2700 4000 5000		B			
			H		150 190 / 225	2700 4000 5000		L			
			H		190 / 225	5000		R			
			W		None 85	S E R RE		T			
			H		150 190 / 225	2700 4000 5000		B			
			H		150 190 / 225	2700 4000 5000		L			
			H		190 / 225	5000		R			