

ALITHERM 400 TBT WINDOW ORDER/QUOTE FORM

Please tick for quote only Page ___ of

Aluminium Direct Fax: 01453 827801 E-mail Orders: sop@customade.co.uk

Company Name (Acc No): _____

Signature: _____

Preferred Delivery Date: _____

Print Name: _____

Order Ref: _____

Date: _____ E-mail confirmation: _____

(Please tick):

Alitherm 400i TBT [] -Contemporary frame - featured sash - **INTERNALLY GLAZED** - square bead

Please Circle Items Required

Please Circle Items Required

| | |
|---|---|
| <p>(Q) = Selection may need to be upgraded to meet Part Q</p> <p>Part Q Compliant: Y / N</p> <p>Colour: White (G) / Grey (7016M) / Black (9005M) / Dual Grey Ex (M) & White Int (G)</p> <p>Handle Colour: White / Gold / Chrome / Black / Grey / Satin Silver / Graphite</p> <p>PAS24: Y / N</p> <p>Trickle Vent Colour: White / Black / Grey / Silver / Grey on white Trickle vent widths 2700mm2 =300mm, 4000mm2=400mm and 5000mm2=600mm</p> <p>Drainage: Face / Concealed</p> | <p>Glass Supply: YES / Unglazed</p> <p>Glass specification width^(Q): 28mm DGU 28.8mm lam DGU^(Q)</p> <p>Triple glazing- Alitherm 400 TBT : 36mm TGU 36.8mm lam TGU^(Q)</p> <p><u>If unglazed please tick above glass thickness for bead type.</u></p> <p>Standard Thermal Rating: Window Energy Rating A externally glazed and B internally glazed with 28mm Clear, 1.2 Softcoat, Argon, Black W/edge (Q)</p> <p>Product U value Special Requirements: _____</p> <p>Astragal bars for 28mm units only - please tick: [] 25mm Flat bar</p> |
|---|---|

Hinge codes: S=Standard Sobinco gear PAS24- Sobinco Safe gear
 T/V Trickle vents require a minimum of 20mm add-on, fixed to the top of the window

| Location | Design (viewed outside, please show T/vents and mullion/transom dimensions) | Qty | Sizes (mm) Including Cills & Add-ons | | Cill | Hinge | Glass Spec (Tgh, Obs, Lead) | Add ons 20mm 30mm 42mm (Minimum of 20mm required with t/vents) | | | Special Requirements |
|----------|---|-----|--------------------------------------|--|------------------|----------------------|-----------------------------|--|---|---|----------------------|
| | | | | | | T/V | | T | B | L | |
| | | | W | | None 85 | S PAS24 | | T | | | |
| | | | H | | 150 190 / 225 | 2700 4000 5000 | | B | | | |
| | | | | | | | | L | | | |
| | | | | | | | | R | | | |
| | | | W | | None 85 | S PAS24 | | T | | | |
| | | | H | | 150 190 / 225 | 2700 4000 5000 | | B | | | |
| | | | | | | | | L | | | |
| | | | | | | | | R | | | |
| | | | W | | None 85 | S PAS24 | | T | | | |
| | | | H | | 150 190 / 225 | 2700 4000 5000 | | B | | | |
| | | | | | | | | L | | | |
| | | | | | | | | R | | | |

| Location | Design (viewed outside , please show T/vents and mullion/transom dimensions) | Qty | Sizes (mm) Including Cills & Add-ons | | Cill | Hinge | Glass Spec (Tgh, Obs, Lead) | Add ons 20mm 30mm 42mm (20, 30 or 42mm required with t/vents) | | | Special Requirements |
|----------|--|-----|--------------------------------------|--|------------------|----------------------|-----------------------------|---|--|--|----------------------|
| | | | | | | T/V | | | | | |
| | | | W | | None 85 | S PAS24 | | T | | | |
| | | | H | | 150 190 / 225 | 2700 4000 5000 | | B | | | |
| | | | H | | | | | L | | | |
| | | | R | | | | | R | | | |
| | | | W | | None 85 | S PAS24 | | T | | | |
| | | | H | | 150 190 / 225 | 2700 4000 5000 | | B | | | |
| | | | H | | | | | L | | | |
| | | | R | | | | | R | | | |
| | | | W | | None 85 | S PAS24 | | T | | | |
| | | | H | | 150 190 / 225 | 2700 4000 5000 | | B | | | |
| | | | H | | | | | L | | | |
| | | | R | | | | | R | | | |
| | | | W | | None 85 | S PAS24 | | T | | | |
| | | | H | | 150 190 / 225 | 2700 4000 5000 | | B | | | |
| | | | H | | | | | L | | | |
| | | | R | | | | | R | | | |
| | | | W | | None 85 | S PAS24 | | T | | | |
| | | | H | | 150 190 / 225 | 2700 4000 5000 | | B | | | |
| | | | H | | | | | L | | | |
| | | | R | | | | | R | | | |
| | | | W | | None 85 | S PAS24 | | T | | | |
| | | | H | | 150 190 / 225 | 2700 4000 5000 | | B | | | |
| | | | H | | | | | L | | | |
| | | | R | | | | | R | | | |