

## HERITAGE 60 RESIDENTIAL/FRENCH DOOR ORDER/QUOTE FORM

Please tick for quote Page \_\_\_ of \_\_\_  
 only

Aluminium Direct Fax: 01453 827801 E-mail Orders: sop@customade.co.uk

Company Name (Acc No): \_\_\_\_\_

Signature: \_\_\_\_\_

Preferred Delivery Date: \_\_\_\_\_

Print Name: \_\_\_\_\_

Order Ref: \_\_\_\_\_

Date: \_\_\_\_\_ E-mail confirmation: \_\_\_\_\_

**Note: 28mm glazing only**  
 : Entrance doors can be coupled to 60mm fixed frames using a 20mm flush coupler  
 : If a door is being coupled to a Heritage 47 window, please note this will be stepped where they are joined by a 25mm wide coupler  
 : Internally beaded only  
 : Standard outerframes can be face or concealed drainage, Open in is face drain only, low thresholds are face drain only

Please Circle Items Required

Please Circle/Tick Items Required

(Q) = Selection may need to be upgraded to meet Part Q

Part Q Compliant: Y / N

Colour: White (G) / Grey (7016M) / Black (9005M) /  
 Dual Grey Ext (M) & White Int (G)

Handle Colour: White / Gold / Chrome / Black  
 Satin Silver / Grey / Graphite / Antique Black

Art Deco handle: Black / White / Brass / Satin Nickel

Hinge Colour: Grey / Black / White

Cylinder: STD 3\* Security Key-Key / 3\* Security Thumb Turn

Drainage: Face / Concealed

Fixed side frame profile width if applicable: 47mm / 60mm

Glass Supply: YES / Unglazed

Flat Panel Supply: YES / Unglazed

Tick which is required:

Door Set Energy Rating: B  C   
 (B only available on french doors)

U value 1.5  1.6

Astragal Bar 25mm Flat bar



(Please draw layout below)

With a handle block you must have solid transoms in the door sash.

Standard threshold  Low threshold

Trickle Vent: White / Black / Grey / Silver / Grey on White

Trickle vent widths 2700mm2=300mm, 4000mm2=400mm and 5000mm2=600mm



Note: Low ali thresholds are not weather rated and therefore not recommended for exposed locations.

Location	Design (viewed outside, please show T/vents, midrail dimensions, master door, astragal bars)	Qty In/Out	Sizes (mm) Including Cills & Add-ons	Cill	Thresh	Glass Spec (Tgh, Obs, Lead)	Addons		Special Requirements
					T/V		20mm	42mm (42mm required with t/vents)	
		Qty:	W	None	Std		T		
					Low Ali		B		
		In	H	150	2700		L		
				190 / 225	4000		R		
		Qty:	W	None	Std		T		
					Low Ali		B		
		In	H	150	2700		L		
				190 / 225	4000		R		
		Qty:	W	None	Std		T		
					Low Ali		B		
		In	H	150	2700		L		
				190 / 225	4000		R		

Location	Design (viewed outside, please show T/vents, midrail dimensions, master door, astragal bars)	Qty In/Out	Sizes (mm) Including Cills & Add-ons		Cill	Thresh	Glass Spec (Tgh, Obs, Lead)	Addons		Special Requirements
						T/V		20mm	42mm (42mm required with t/vents)	
		Qty:	W		None	Std		T		
					85	Low Ali		B		
		In	H		150	2700		L		
		Out			190 / 225	4000		R		
						5000				
		Qty:	W		None	Std		T		
					85	Low Ali		B		
		In	H		150	2700		L		
		Out			190 / 225	4000		R		
						5000				
		Qty:	W		None	Std		T		
					85	Low Ali		B		
		In	H		150	2700		L		
		Out			190 / 225	4000		R		
						5000				
		Qty:	W		None	Std		T		
					85	Low Ali		B		
		In	H		150	2700		L		
		Out			190 / 225	4000		R		
						5000				
		Qty:	W		None	Std		T		
					85	Low Ali		B		
		In	H		150	2700		L		
		Out			190 / 225	4000		R		
						5000				
		Qty:	W		None	Std		T		
					85	Low Ali		B		
		In	H		150	2700		L		
		Out			190 / 225	4000		R		
						5000				
		Qty:	W		None	Std		T		
					85	Low Ali		B		
		In	H		150	2700		L		
		Out			190 / 225	4000		R		
						5000				