

ALITHERM 400 WINDOW ORDER/QUOTE FORM

Please tick for quote only Page ___ of

Aluminium Direct Fax: 01453 827801 E-mail Orders: sop@customade.co.uk

Company Name (Acc No): _____

Signature: _____

Preferred Delivery Date: _____

Print Name: _____

Order Ref: _____

Date: _____ E-mail confirmation: _____

(Please tick): Alitherm 400 Hybrid [] -Contemporary frame -flat sash -**INTERNALLY GLAZED SASH / EXTERNALLY GLAZED FIXED FRAMES** -square bead
 Alitherm 400i [] -Contemporary frame - flat sash - **INTERNALLY GLAZED** - square bead with dummy sashes
 Alitherm 400x [] -Contemporary frame - flat sash - **EXTERNALLY GLAZED** - square bead

Note: The Alitherm 400i and Hybrid glazed window systems are a 28mm tap in quickglaze bead as standard.

Note: Alitherm 400x windows and internally beaded Alitherm 400i triple glazed windows are wedge gasketed as standard.

Please Circle Items Required

Please Circle Items Required

(Q) = Selection may need to be upgraded to meet Part Q
Part Q Compliant: Y / N 400x/Hybrid Glass locks^(Q): Y / N
Colour: White (G) / Grey (7016M) / Black (9005M) / Dual Grey Ex (M) & White Int (G)
Handle Colour: White / Gold / Chrome / Black / Grey / Satin Silver / Graphite / Antique Black (Monkey tail)
Stayguards^(Q): Y / N
Trickle Vent Colour: White / Black / Grey / Silver / Grey on white
 Trickle vent widths 2700mm²=300mm, 4000mm²=400mm and 5000mm²=600mm
Drainage: Face / Concealed

Glass Supply: YES / Unglazed
Glass specification width^(Q): 28mm DGU 28.8mm lam DGU
Triple glazing- Alitherm 400i only: 40mm TGU 40.8mm lam TGU
If unglazed please tick above glass thickness for gasket type.
 For externally glazed triple glazing use our REAL System 2 windows
Standard Thermal Rating:
 Window Energy Rating A externally glazed and B internally glazed with 28mm Clear, 1.2 Softcoat, Argon, Black W/edge (Q)
Product U value Special Requirements: _____
Astragal bars for 28mm units only - please tick: [] 25mm Flat bar

Hinge codes: S=Standard / E=Egress easy / R=Restrictor / RE=Restrictor Egress (TRI R90)

T/V Trickle vents require a 30 or 42mm add-on, fixed to the top of the window

Location	Design (viewed outside, please show T/vents and mullion/trans dimensions)	Qty	Sizes (mm) Including Cills & Add-ons		Cill	Hinge		Glass Spec (Tgh, Obs, Lead)	Addons (30 or 42mm required with t/vents)			Special Requirements
						S	E		20mm	30mm	42mm	
			W		None 85	S	E		T			
			H		150 190 / 225	2700	4000	5000	L			
			W		None 85	S	E		T			
			H		150 190 / 225	2700	4000	5000	L			
			W		None 85	S	E		T			
			H		150 190 / 225	2700	4000	5000	L			
			W		None 85	S	E		T			
			H		150 190 / 225	2700	4000	5000	L			

Location	Design (viewed outside , please show T/vents and mullion/trans dimensions)	Qty	Sizes (mm) Including Cills & Add-ons		Cill	Hinge	Glass Spec (Tgh, Obs, Lead)	Addons 20mm 30mm 42mm (30 or 42mm required with t/vents)			Special Requirements
						T/V					
			W		None 85	S E R RE		T			
			H		150 190 / 225	2700 4000 5000		B			
			H					L			
			R					R			
			W		None 85	S E R RE		T			
			H		150 190 / 225	2700 4000 5000		B			
			H					L			
			R					R			
			W		None 85	S E R RE		T			
			H		150 190 / 225	2700 4000 5000		B			
			H					L			
			R					R			
			W		None 85	S E R RE		T			
			H		150 190 / 225	2700 4000 5000		B			
			H					L			
			R					R			
			W		None 85	S E R RE		T			
			H		150 190 / 225	2700 4000 5000		B			
			H					L			
			R					R			
			W		None 85	S E R RE		T			
			H		150 190 / 225	2700 4000 5000		B			
			H					L			
			R					R			