

**ALITHERM 400 TBT WINDOW ORDER/QUOTE FORM**

Please tick for quote only Page \_\_\_ of \_\_\_

Aluminium Direct Fax: 01453 827801 E-mail Orders: sop@real-aluminium.co.uk

Company Name (Acc No): \_\_\_\_\_  
 Preferred Delivery Date: \_\_\_\_\_  
 Order Ref: \_\_\_\_\_

Signature: \_\_\_\_\_  
 Print Name: \_\_\_\_\_  
 Date: \_\_\_\_\_ E-mail confirmation: \_\_\_\_\_

**(Please tick):**  
 Alitherm 400i TBT [ ] -Contemporary frame - featured sash - **INTERNALLY GLAZED** - square bead

**Please Circle Items Required**

**Please Circle Items Required**

<p>(Q) = Selection may need to be upgraded to meet Part Q</p> <p><b>Part Q Compliant:</b> Y / N</p> <p><b>Colour:</b> White (G) / Grey (7016M) / Black (9005M) / Dual Grey Ex (M) &amp; White Int (G)</p> <p><b>Handle Colour:</b> White / Gold / Chrome / Black / Grey / Satin Silver / Graphite</p> <p><b>PAS24:</b> Y / N</p> <p><b>Trickle Vent Colour:</b> White / Black / Grey / Silver / Grey on white              Trickle vent widths 2700mm2 =300mm, 4000mm2=400mm and 5000mm2=600mm</p> <p><b>Drainage:</b> Face / Concealed</p>	<p><b>Glass Supply:</b> YES / Unglazed</p> <p><b>Glass specification width<sup>(Q)</sup>:</b> 28mm DGU 28.8mm lam DGU<sup>(Q)</sup></p> <p><b>Triple glazing- Alitherm 400 TBT :</b> 36mm TGU 36.8mm lam TGU<sup>(Q)</sup></p> <p><b><u>If unglazed please tick above glass thickness for bead type.</u></b></p> <p><b>Standard Thermal Rating:</b>              Window Energy Rating A externally glazed and B internally glazed with 28mm Clear, 1.2 Softcoat, Argon, Black W/edge (Q)</p> <p><b>Product U value Special Requirements:</b> _____</p> <p><b>Astragal bars for 28mm units only - please tick:</b> [ ] 25mm Flat bar</p>
---	---

Hinge codes: S=Standard Sobinco gear PAS24- Sobinco Safe gear  
 T/V Trickle vents require a minimum of 20mm add-on, fixed to the top of the window

Location	Design (viewed outside, please show T/vents and mullion/transom dimensions)	Qty	Sizes (mm) Including Cills & Add-ons		Cill	Hinge	Glass Spec (Tgh, Obs, Lead)	Add ons 20mm 30mm 42mm (Minimum of 20mm required with t/vents)			Special Requirements
						T/V					
			W		None 85	S PAS24		T			
			H		150 190 / 225	2700 4000 5000		B			
								L			
								R			
			W		None 85	S PAS24		T			
			H		150 190 / 225	2700 4000 5000		B			
								L			
								R			
			W		None 85	S PAS24		T			
			H		150 190 / 225	2700 4000 5000		B			
								L			
								R			

Location	Design ( <b>viewed outside</b> , please show T/vents and mullion/transom dimensions)	Qty	Sizes (mm) Including Cills & Add-ons		Cill	Hinge	Glass Spec (Tgh, Obs, Lead)	Add ons 20mm 30mm 42mm (20, 30 or 42mm required with t/vents)			Special Requirements
						T/V					
			W		None 85	S PAS24		T			
			H		150 190 / 225	2700 4000 5000		B			
			H					L			
			H					R			
			W		None 85	S PAS24		T			
			H		150 190 / 225	2700 4000 5000		B			
			H					L			
			H					R			
			W		None 85	S PAS24		T			
			H		150 190 / 225	2700 4000 5000		B			
			H					L			
			H					R			
			W		None 85	S PAS24		T			
			H		150 190 / 225	2700 4000 5000		B			
			H					L			
			H					R			
			W		None 85	S PAS24		T			
			H		150 190 / 225	2700 4000 5000		B			
			H					L			
			H					R			