

VISOGLIDE PLUS ORDER/QUOTE FORM

Aluminium Direct Fax: 01453 827801 E-mail Orders: sop@real-aluminium.co.uk

Please tick for quote only

Page ___ of ___

Company Name (Acc No): _____

Signature: _____

Preferred Delivery Date: _____

Print Name: _____

Order Ref: _____

Date: _____ Contact Numbers: _____

Please e-mail confirmation to: _____

Please Circle Items Required

Part Q Compliant: Y / N (If yes, locks will be upgraded at an additional charge)

Outer frame: Standard / Internal upstand

Colour: White (G) / Grey (7016M) / Black (9005M) / Dual Grey Ex (M) & White Int (G)

Wind loading reqd: 800 pascals (default) or _____ pascals or Site postcode for wind load calc _____.

Sliding door on: inside track (default) / outside track

Cill: None Two Track 150mm / 190mm
 Three Track 235mm* / 300mm

Interlocking Mullion: Standard 83mm / Slim 35mm

Handle Type: D / Lever-Lever
 Internal Only / Internal & External

Threshold: Two Track / Three Track
 Two Track internal upstand / Three Track internal upstand

(Q) = Selection may need to be upgraded to meet Part Q

Handle Colour: White / Black / Grey / Satin Silver
 (Note: Chrome n/a)
Glass Supply: Glazed / Unglazed

Glass Spec: Double Glazing 28mm T 28.8mm Lam
 Triple Glazing 36mm T 36.8mm Lam

Standard Thermal Rating:
 Door Energy Rating C with 28mm Cl tgh, 1.2 Softcoat, Argon, Black W/edge

Glass Special Requirements _____

Nickel Cylinder^(Q): STD Key-Key / STD Thumb Turn
 3* Security Key-Key / 3* thumb Turn

Trickle Vent(s) fitted in 42mm add-on: QTY []

Trickle Vent Size EA: None / 2700 / 4000 / 5000

TV Colour: White / Black / Grey / Silver / Grey on White

Deliver: Assembled * / Flat pack frame + sashes

*You will need to ensure able bodied people are available to assist with offloading at the delivery address. If this requirement is not met you will be charged for the redelivery of the product.

Please indicate style by ticking box ('H' indicates handle position)

Interlocking mullion Bi-parting mullion

As shown Reverse

As shown Reverse

As shown Reverse

As shown Reverse

As shown Reverse

As shown Reverse

As shown Reverse

As shown Reverse

Key Limits

Max sash width for 4mm tgh = 1400mm (approx)
 Max sash width for 6mm tgh = 1700mm (approx)
 Max sash height = 2500mm
 Max sash weight = 200kg

Key Dimensions

Std 2 track frame is 99mm / 3 track frame is 165.5mm
 Internal upstand 2 track frame is 116mm / 3 track frame is 182.5mm
 Standard track plaster cover 43mm
 Internal upstand track plaster cover 53mm
 Frame to glass sightline 117.5mm
 Bi-parting mullion sightline 156mm

*Note: a 235mm cill is a two piece cill 150+85.

Qty	Sizes (mm) Including Cills & Add-ons	42mm Add-ons (required with t/vents)	Special Requirements
W		T	
		B	
H	(max 2500mm)	L	
		R	
W		T	
		B	
H	(max 2500mm)	L	
		R	

Note: Viewed externally