

VISOFOOLD 1000 QUICKGLAZE BI-FOLD DOOR ORDER/QUOTE

Aluminium Direct Fax: 01453 827801 E-mail Orders: sop@customade.co.uk

Please tick for quote only

Company Name (Acc No): _____

Signature: _____

Preferred Delivery Date: _____

Print Name: _____

Order Ref: _____

Date: _____ E-mail _____

confirmation: _____

Please Circle Items Required

<p>(Q) = Selection may need to be upgraded to meet Part Q</p> <p>System : Slim sash quickglaze Medium Sash: quickglaze / wedge gasketed</p> <p>Outer frame: STD DV14 (70mm frame) / DV17 (82mm frame)</p> <p>Colour: White (G) / Grey (7016M) / Black (9005M) / Dual Grey Ext (M) & White Int (G)</p> <p>Master Door Handle: Lever-Lever only</p> <p>Slave Door Handle (if applicable): Lever-Lever / Intermediate</p> <p>Intermediate pop out Handles (Slim sash only): Locking / Non-Locking</p> <p>Intermediate standard handles (Medium sash only): Locking / Non-Locking</p> <p>Lever-Lever Handle Colour: White / Black / Chrome Grey / Graphite / Satin Silver / Gold</p> <p>Intermediate Handle Colour: White / Black / Grey (recommended)</p> <p>Hinge Colour: White / Black (recommended)</p> <p>'D' Pull Handle (on hinge): White / Black / Grey</p> <p>Magnetic Hold Open Catch: None / White / Black / Grey / Chrome</p> <p>Addon Trickle Vent: None / White / Black / Grey / Silver / Grey on White</p> <p>Trickle Vent Equivalent area: 2700 / 4000 / 5000 Number TV's:</p> <p>Trickle vent widths 2700mm2 =300mm, 4000mm2=400mm and 5000mm2=600mm</p>	<p>2200 EA Sash Flush Trickle Vent: None / White / Black / Grey / Grey on white</p> <p>Number of Sash Flush Trickle vents: _____ (Sash Flush Trickle Vent EA 2200mm2)</p> <p>Part Q Compliant: Y / N</p> <p>Glass Supply: YES / Unglazed</p> <p>Glass Spec: Double Glazing 28mm 28.8mm lam Triple Glazing 44mm 44.8mm lam</p> <p><i>If unglazed please tick glass thickness for gasket type. Note:Triple glazing will require wedge gaskets.</i></p> <p>Standard Thermal Rating: Door Energy Rating C with 28m Cl tgh, 1.2 Softcoat, Argon, Black W/edge (Q)</p> <p>Glass Special Requirements: _____</p> <p>Product U value Special Requirements: _____</p> <p>Threshold: [] DV14 51.5mm rebated [] DV17 51.5mm (82mm deep) [] DV171 15mm low threshold open in [] DV271 15mm low threshold open out [] DV173 20mm low threshold open in and out [] DV176 integrated cill (175mm) open out only</p> <p>Note: integrated cill requires DV17 outer frame (82mm deep frame- 30mm addon not compatible)</p> <p>Delivery : ASSEMBLED FLAT PACK</p> <p><i>*You will need to ensure able bodied people are available to assist with offloading at the delivery address. If this requirement is not met, you will be charged for the redelivery of the product.*</i></p> <p><i>Note: Low thresholds not weather rated and 3* cylinders as standard Sash flush trickle vents are fitted into the top of the door sashes.</i></p>
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Note: Mullion dimensions can vary depending on style. External access is only available on bi-folds which have a 'lead' door.

Location	Design (viewed from outside, show master door)	Design (in open position, viewed from above)	Qty	Cill	Sizes (mm) Including Cills & Add-ons	Addons			Special Requirements / mark on positions of sash flush trickle vents on required sashes.
						20mm	30mm	42mm	
	Open in / Open out			None Integrated 85 / 150 190 / 225	W (max 1200mm per sash)	T			
						B			
					H (max 2500mm)	L			
						R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W (max 1200mm per sash)	T			
						B			
					H (max 2500mm)	L			
						R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W (max 1200mm per sash)	T			
						B			
					H (max 2500mm)	L			
						R			

Location	Design (viewed from outside, show master door)	Design (in open position, viewed from above)	Qty	Cill	Sizes (mm) Including Cills & Add-ons	Addons		Special Requirements / mark on positions of sash flush trickle vents on required sashes.
						20mm	30mm 42mm (30 or 42mm required with T/vents with the exception of sash flush trickle vents)	
	Open in / Open out			None Integrated 85 / 150 190 / 225	W (max 1200mm per sash)	T		
B								
H (max 2500mm)					L			
					R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W (max 1200mm per sash)	T		
B								
H (max 2500mm)					L			
					R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W (max 1200mm per sash)	T		
B								
H (max 2500mm)					L			
					R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W (max 1200mm per sash)	T		
B								
H (max 2500mm)					L			
					R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W (max 1200mm per sash)	T		
B								
H (max 2500mm)					L			
					R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W (max 1200mm per sash)	T		
B								
H (max 2500mm)					L			
					R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W (max 1200mm per sash)	T		
B								
H (max 2500mm)					L			
					R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W (max 1200mm per sash)	T		
B								
H (max 2500mm)					L			
					R			
	Open in / Open out			None Integrated 85 / 150 190 / 225	W (max 1200mm per sash)	T		
B								
H (max 2500mm)					L			
					R			